12/6/2024



| Product name VEGAB | AR 28 |
|----------------------|-----------|
| Model code B28.XX | XXC3AGSCB |
| Order number PP - 22 | 2 2FV |

| Quantity | 1 | |
|--------------------------|---|--|
| Production period (days) | 3 | |

Pressure sensor

Application area

VEGABAR 28 is a universal pressure transmitter with ceramic measuring cell for measurement of gases, vapours and liquids up to 130 °C. The optional universal connection for hygienic adapters ensures reduced installation effort and leaner stock keeping.

Your benefit

- High system availability due to highest overload and vacuum resistance of the ceramic measuring cell
 Easy integration into control systems through IO-Link communication
- Coloured 360° status display, adjustable
- Comfortable wireless setup and diagnostics with smartphone

| Explosion protection | ХХ | for Ex-free area (CE, UKCA, RCM, c-UL-us) |
|--|----|---|
| Ship approval | Х | without |
| Foodstuff/Pharmaceutical certificate | Х | without |
| Process fitting / Material | C3 | Thread G½, ISO228-1; front-flush / 316L |
| Measuring cell seal / Process temperature | Α | FKM (VP2/A) / -20+130°C (-4+266°F) |
| Measuring range | G | relative, 0+10.0bar (0+1000kPa) |
| Electrical connection / Protection | S | 4-pole plug connection ISO4400 M16 / IP65 |
| Electronics | С | Three-wire: transistor, 420 mA (active) |
| 360° status display | | with |
| Customer-specific adjustment | | No |
| Sensor setting via smartphone and VEGA Tools app | В | with |
| Additional cleaning procedure | | without |
| Characteristics, test certific | | without |
| Material certificate | | without |
| Measurement loop identification label | | without |
| Min. process pressure in bar | | -1 |
| Max. process pressure in bar | | 60 |
| Customs tariff number (HS code) | | 90262020 |
| Software version | | Current version |