

Product name	VEGADIS 82
Model code	DIS82.ACXKIMACX
eID	SG43282253
Quantity	1
Production period (days)	3

### External display and adjustment unit for 4 ... 20 mA/HART sensors

#### Application area

The VEGADIS 82 is suitable for measured value indication and adjustment of 4 ... 20 mA sensors, optionally with HART protocol. The instrument can be looped in any position directly in the signal cable. It operates as pure display instrument in a 4 ... 20 mA current loop. Optionally sensors with HART protocol can be operated. The instrument is particularly designed for VEGAPULS (C) 11, 21, 22, 23, 31 and VEGAWELL 52 sensors.

#### Your benefit

- Time and cost savings during the parameter adjustment on site with PLICSCOM
- Reliable and simple adjustment through clear text indication with graphic support
- Universal use through HART standard parameters
- Optional possibility of a wireless adjustment with smartphone/tablet/PC as well as magnet pen adjustment through housing lid with window

Scope	<b>A</b>	Europe
Approval	<b>C</b>	ATEX II 1G, 2G Ex ia IIC T6 Ga, Gb
Electronics	<b>X</b>	Two-wire 4 ... 20 mA
Optional overvoltage protection		without
Housing	<b>K</b>	Plastic
Protection	<b>I</b>	IP66/IP67 NEMA 4X
Cable entry / Connection	<b>M</b>	M20x1.5 / Cable gland PA black (ø5-9mm), standard
Indicating/adjustment module (PLICSCOM)	<b>A</b>	Mounted
Language of the PLICSCOM menu		TR - Turkish
Mounting	<b>C</b>	for carrier rail and wall mounting with plastic housing
Certificates	<b>X</b>	No
Suitable for tropical regions		without
Type label / Measurement loop identification label		of foil / without
Operating instructions		TR - Turkish
Number of operating instructions		0
Customs tariff number (HS code)		85312020